

## PRODUCT SPECIFICATION SP1410UV (AU Size)—UV Stabilised

### MATERIAL

Injection Moulded – Co-Polymer Polypropylene  
100% Recycled Feedstock  
0.3% UV Stabiliser

### DIMENSIONS

Length : 1420mm +2mm / -0mm  
Width : 1090mm +2mm / -0mm  
Thickness : 3.0mm (Nested, 7.5mm on edge profile)  
Weight : 4.2Kg

### PROFILE

Operating Temperature : 0°C – 50°C  
Conductivity :  $10^{13}$  Ohmcm  
UV Performance : 70K Langley  
Chemical Resistance : Acids, Alkalis, Alcohols,  
Grease, Oils & Ketones

### CONFORMANCE

90/128/EEC : Directive; Plastics in contact with foodstuffs  
92/39/EEC : Directive; Plastics in contact with foodstuffs  
93/9/EEC : Directive; Plastics in contact with foodstuffs  
95/3/EEC : Directive; Plastics in contact with foodstuffs

### PACKAGING SPECIFICATION

Qty Per Pallet	Standard 300	Container 313
Per Load	4800	5008
Pallet Weight	1280Kg	1335Kg
Pallet Height	1050mm	1089mm
Packaging	Heavy Duty shrink wrap, with fuse sealed base sheet.	